

DIGBY BUILT

Dealer Info Sheet

Specs:

- Sections are 2" thick aluminum constructed frames
- Full view tempered glass. Sizes: 1/8" and ½"
- 1/4" thick laminate glass will be available in white & black
- Groove and tongue section joints with a compression seal
- Section heights: Will all be proportionate
- Bolted stiles: end stile is 4" double end stile is 8" center stile is 2"
- Double-end hinges will be used on any door over 16' 3" wide
- Rail on top and bottom is 4"; intermediates are 1½"
- Heavy-duty hardware; 14-gauge hinges, 10 roller balls
- 15" radius mount bracket track
- Anodize: Black, Bronze, Clear
- Painted: White

Options:

- Low headroom 2" and 3"
- Long stem rollers
- Glass types 1/8" tempered: clear, light grey, obscure, dark grey, bronze, and satin etch
- Glass Laminates 1/4": Black and white
- Ask about options for insulated glass
- Odd width section sizes in 1" increments
- Inside slide lock
- Powder coating: Frame and/or hardware
- 20" Radius track
- Chain hoist available high lift, pitch, and vertical lift
- High cycle springs
- 3" steel rollers
- 3" long stem rollers
- 2" & 3" reverse angle track
- 2" bracket mount set (12" or 15" radius)
- 2" bracket mount set (20" radius)
- Extra strut available
- Reverse angle guide seal
- Top flat seal weather strip
- Solid shaft